

## 性能表（起重機使用の参考値）

下記、性能表は起重機仕様の巻上荷重の参考値です。

バケット仕様はクレーン直巻能力を超える巻上荷重は直巻能力に制限する。

（作業半径：m 巻上荷重：t）

機種	シブ長	75°		70°		60°		50°		40°		30°	
	傾斜角度	作業半径	巻上荷重	作業半径	巻上荷重	作業半径	巻上荷重	作業半径	巻上荷重	作業半径	巻上荷重	作業半径	巻上荷重
SE202 LGP	19	7.0	23.8	8.6	18.0	11.6	12.3	14.3	9.6	16.7	8.0	18.6	7.1
	20	7.3	22.6	8.9	17.1	12.1	11.7	15.0	9.1	17.4	7.6	19.4	6.7
	21	7.5	21.5	9.3	16.3	12.6	11.1	15.6	8.7	18.2	7.3	20.3	6.4
SE251 LGP	20	7.4	29.5	9.0	22.3	12.2	15.3	15.1	11.9	17.5	10.0	19.5	8.8
	21	7.6	28.1	9.4	21.3	12.7	14.6	15.7	11.3	18.3	9.5	20.4	8.4
	22	7.9	26.8	9.7	20.3	13.2	13.9	16.3	10.8	19.1	9.1	21.3	8.0
SE302 LGP	21	7.8	34.4	9.6	26.0	12.9	17.8	15.9	13.8	18.5	11.6	20.6	10.3
	22	8.1	32.8	9.9	24.8	13.4	17.0	16.5	13.2	19.2	11.1	21.4	9.8
	23	8.3	31.4	10.2	23.8	13.9	16.3	17.2	12.6	20.0	10.6	22.3	9.4
SE360 LGP	22	8.1	40.0	10.0	30.3	13.4	20.7	16.6	16.1	19.3	13.5	21.5	12.0
	23	8.4	38.3	10.3	29.0	13.9	19.8	17.2	15.4	20.1	12.9	22.4	11.4
	24	8.7	36.7	10.6	27.7	14.4	19.0	17.9	14.8	20.8	12.4	23.2	11.0
SE360 LGP-S	25	8.9	40.1	11.0	30.4	14.9	20.8	18.5	16.2	21.6	13.6	24.1	12.0
	26	9.2	38.6	11.3	29.2	15.4	20.0	19.2	15.5	22.4	13.0	25.0	11.5
	27	9.4	37.2	11.7	28.1	15.9	19.2	19.8	15.0	23.1	12.6	25.8	11.1
SE400 LGP	26	9.3	47.8	11.5	36.2	15.6	24.7	19.3	19.3	22.5	16.2	25.1	14.3
	27	9.6	46.0	11.8	34.8	16.1	23.8	20.0	18.5	23.3	15.6	26.0	13.8
	28	9.8	44.4	12.2	33.6	16.6	23.0	20.6	17.9	24.0	15.0	26.8	13.3
SE500 LGP	28	9.9	52.7	12.2	39.9	16.7	27.3	20.6	21.2	24.1	17.8	26.9	15.8
	29	10.2	50.9	12.6	38.5	17.2	26.3	21.3	20.5	24.9	17.2	27.8	15.2
	30	10.4	49.2	12.9	37.2	17.7	25.5	21.9	19.8	25.6	16.6	28.6	14.7
SE600 LGP-S	32	11.0	57.9	13.7	43.8	18.8	30.0	23.3	23.3	27.3	19.6	30.5	17.3
	33	11.3	56.1	14.0	42.5	19.3	29.1	24.0	22.6	28.0	19.0	31.3	16.8
	34	11.5	54.5	14.4	41.2	19.8	28.2	24.6	21.9	28.8	18.4	32.2	16.3
EP2800	20	7.4	32.4	9.0	24.5	12.2	16.7	15.1	13.0	17.5	10.9	19.5	9.7
	21	7.6	30.8	9.4	23.3	12.7	16.0	15.7	12.4	18.3	10.4	20.4	9.2
	22	7.9	29.4	9.7	22.3	13.2	15.2	16.3	11.8	19.1	9.9	21.3	8.8
EP3600	25	8.9	40.1	11.0	30.4	14.9	20.8	18.5	16.2	21.6	13.6	24.1	12.0
	26	9.2	38.6	11.3	29.2	15.4	20.0	19.2	15.5	22.4	13.0	25.0	11.5
	27	9.4	37.2	11.7	28.1	15.9	19.2	19.8	15.0	23.1	12.6	25.8	11.1
EP4000	26	9.3	47.8	11.5	36.2	15.6	24.7	19.3	19.3	22.5	16.2	25.1	14.3
	27	9.6	46.0	11.8	34.8	16.1	23.8	20.0	18.5	23.3	15.6	26.0	13.8
	28	9.8	44.4	12.2	33.6	16.6	23.0	20.6	17.9	24.0	15.0	26.8	13.3
EP5000	28	9.9	52.7	12.2	39.9	16.7	27.3	20.6	21.2	24.1	17.8	26.9	15.8
	29	10.2	50.9	12.6	38.5	17.2	26.3	21.3	20.5	24.9	17.2	27.8	15.2
	30	10.4	49.2	12.9	37.2	17.7	25.5	21.9	19.8	25.6	16.6	28.6	14.7
EP6000	32	11.0	57.9	13.7	43.8	18.8	30.0	23.3	23.3	27.3	19.6	30.5	17.3
	33	11.3	56.1	14.0	42.5	19.3	29.1	24.0	22.6	28.0	19.0	31.3	16.8
	34	11.5	54.5	14.4	41.2	19.8	28.2	24.6	21.9	28.8	18.4	32.2	16.3